

DWG NO.
C-101086

TOP-LINK

- Notes:
- Material:
 - 1)Puncher & Body : CuZn36 Pb3, H02 (C36000) or CuZn39 PB3 or CuZn38 PB2.
 - 2)Spring : Stainless steel wire
- 2 Plating
 - 1)Body: Gold plating over Nickle plating
 - 2)Puncher: Gold plating over Nickle plating
- 3 Mechanical
 - 1)Total stroke : 0.75mm
 - 2)Durability: 10,000 cycle min.
- 4 Electrical
 - 1)Contact resistance: 30mOhm Max.
 - 2)Operating voltage: 36VDC

USED ON

	NEW		2007/08/01
LTR	REVISION RECORD	APVD	DATE

DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED		MATL		HT TR	—	FIN	— 
0	= ±	DWN		APVD	Lansing	<i>Top-Link Electronics</i>	Top-Link Electronics Ltd.
0.0	= ±0.10	Benny			REL		
0.00	= ±	CHK					
0.000	= ±	Andy					
ANGLE: ±1°							
SURF TEXTURE: 32/ 		NAME					
REMOVE BURRS, BREAK SHARP EDGES TO .05 MAX		PG-1.0-1.0-2.0-0.4-1.5-2.6-3.4					
DO NOT SCALE PRINT		SCALE	A4	DWG NO.	C-101086	SHEET 1 OF 1	REV A
		1:1					

101086-1
PART NUMBER