



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.




DWG NO.
C-101150

LDC
-
DIST
-



TOP-LINK



- Notes:
- Material:
- 1)Plunger & Body : CuZn36 Pb3, H02 (C36000)
or CuZn39 PB3 or CuZn38 PB2.
- 2)Spring : Stainless steel wire
- 2 Plating
- 1)Body: 0.1um Gold plating over min. 1.25um Nickle plating
- 2)Plunger: 0.4um Gold plating over min. 1.25um Nickle plating
- 3 Mechanical
- 1)Total stroke : 1.5mm
- 2)Durability: 10,000 cycle min.
- Electrical
- 1)Contact resistance: 30mOhm Max.
- 2)Operating voltage: 36VDC

DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED			
0	= ± -		
0.0	= ±0.10		
0.00	= ± -		
0.000	= ±		
ANGLE: ±1°			
SURF TEXTURE: 32/			
REMOVE BURRS, BREAK			
SHARP EDGES R0.05 MAX			
DO NOT SCALE PRINT			
MATL	1	HT TR	FIN
DWN		APVD	
Benny		Lansing	
CHK		REL	
Andy			
NAME	POGO PIN		
SCALE	1:1	A4	DWG NO.
			C-101150
			PG-0.9-2.3-2.0-0.5-1.5-3.5-5.5
			Top-Link Electronics Ltd.
			101150-1
			PART NUMBER
			1 OF 1
			REV A

USED ON

-