


proposal



DIST

Update	2012/09/17
NEW	2008/04/07
Revision record.	Date.

Top-Link Electronics Ltd.	Type	Customer drawing	Unit	mm	Weight
TOLERANCES UNLESS OTHER SPECIFIED	DWN:	Cai wonlu	APVD:		
0.0 = ±0.15	CHK:		REL:		
0.00 = ±0.10	Angle: ±1°				
0.000 = ±0.005	SURF. TEXTURE:				
REMOVE SHARP EDGES	REMOVE BURRS				
BREAK MAX. DO NOT SCALE PRINT.					
POGO PIN	Name				
Scale 1:1	Size A4	DWG No.	C-101184	Page 1/1	Rev. B

101184-1
PART NUMBER

Table 1 Mechanical performance		
working height	9.8mm	120gf Min
Durability	10000cycle	

Item	Part name	Q'ty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.4um plating Ni 2.5um
3	Spring	1	Stainless steel wire	
4				
5				

Not

1 Dempnstions shall be interpreted per ASME Y14.5M.

2 Mechanical performance(See the table 1)

<2.1> The force is the average of forces obtained when plunger goes downwards and upwards.

3 Electrical performance

Resistance: 30mOhm Max.Current rating: 2.0A

4 RoHS compliant.

TOP LINK