



Notes: Material:

- 1)Plunger & Body : Brass
- 2)Spring : Stainless steel wire
- 2 Plating
 - 1)Body: 0.1um Gold plating over min. 1.4um Nickle plating
 - 2)Plunger: 0.4um Gold plating over min. 1.4um Nickle plating
- 3 Mechanical
 - 1)Total stroke : 1.4mm
 - 2)Durability: 10,000 cycle min.
- 4 Electrical
 - 1)Contact resistance: 30mOhm Max.
 - 2)Operating voltage: 36VDC
 - 3)Operating temperature: -40°C to 100°C

	NEW		2008/10/15
LTR	REVISION RECORD	APVD	DATE

DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED		MATL	HT TR	FIN
0	= ±		—	
0.0	= ±0.15			
0.00	= ±0.10			
0.000	= ±	CHK	Jlm	
ANGLE: ±1°				
SURF TEXTURE: 32/		NAME		
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX		PGGD PIN		
DO NOT SCALE PRINT		SCALE	1:1	DWG NO. C-101244 SHEET 1 OF 1 REV A

101244-1	PART NUMBER
----------	-------------