



Table 1 Mechanical performance		
Max. working height	10.50mm	85±20gf <3.1>
Min. working height	8.80mm	215±50gf
Durability	10000cycle	

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 3.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- 3.2>Warning:Working height are not permitted to be less than Min working height.
- 3 Electrical performance
- Resistance:50mOhm Max.Current rating: 2.0A
- 4 Packaging Spec.Conformance to EIA 481
- 5 RoHS compliant.

Recommended solder paste thickness is 0.10 mm									
Recommended PCB Layout									
DIST				Top-Link Electronics Ltd.					
---				TOLERANCES UNLESS OTHER SPECIFIED					
---				0.0 = ± 0.15					
---				0.00 = ± 0.10					
---				0.000 = ± 0.005					
---				Angle: ±1°					
---				SURF TEXTURE: REMOVE BURRS.					
---				BREAK SHARP EDGES R0.05 MAX DO NOT SCALE PRINT.					
DIST				Type		Unit		Weight	
---				Customer drawing		mm			
---				DWG No.		C-110165		Page 1/1	
---				Rev.		A1			
---				4		3		2	