


THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.







RECOMMEND PCB LAYOUT(TOP VIEW)
Layout Tolerance: ± 0.05mm

Notes:
1 Dimensions shall be interpreted per ASME Y14.5M
2 Mechanical performance(See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards
<2.2>Warning:Working height are not permitted to be less than Min working height
3 Electrical performance
<3.1>Current rating: 2.0A
<3.2>Voltage rating: 36VAC/DC
<3.3>Dynamic Resistance:30mOhm Max (between max and min working height)
4 Environmental performance
<4.1> RoHS compliant
<4.2>Operating Temperature range:-40°C~+85°C
<4.3>Storage Temperature range:-40°C~+85°C
<4.4>Withstanding High Temperature:260°C/10Sec
5 Packaging:Carrier tape

Table 1:Mechanical performance		
Max working height	7.0mm	35gf min
Working Height	6.6mm	60±20gf
Durability	10000 Cycles Min.	

Item	Part Name	Q'TY	Material	Finish
5	CAP	1pcs	High temp.Plastic; UL94 V-0 Color Black	--------
4	Body	4pcs	Leaded Brass	Au 0.1um min plated over 1.4um min Ni
3	Plunger	4pcs	Leaded Brass	Au 0.4um min plated over 1.4um min Ni
2	Spring	4pcs	Stainless steel wire	--------
1	Housing	1pcs	High temp.Plastic; UL94 V-0 Color gray	--------

Item	Revision record	Date
4	Modify Release	2017.05.17
3	Working height was changed	2015.10.08

Top-Link Electronics Ltd.
TOLERANCES UNLESS OTHER SPECIFIED
0. = ± -
0.0 = ± 0.15
0.00 = ± 0.10
0.000= ± -
Angle: ±1°
SURF TEXTURE:
REMOVE BURRS.
BREAK SHARP EDGES
R0.05 MAX.DO NOT SCALE PRINT.

Type: Customer drawing		Unit: mm	top-link
DRW: Jimmy	APRD: Alex		
CHK: Henry	REL:		
Name: 4 Pin Pogo Pin Connector			
Scale: 1:1	Size: A4	Part NO.: 10101041483	Page: 1/1 Rev: 4

D C B A
4 3 2 1