



TOP-LINK

Item	Part name	Q'ty/Ea'	Material	Finish
1	HSG	1	High temp. Plastic UL94 V-0 Color Black	_____
2	Body	4	Leaded Brass	Gold plating over Nickel plating
3	Plunger	4	Leaded Brass	Gold plating over Nickel plating
4	Spring	4	Stainless steel wire	_____
5				

Table 1 Mechanical performance			
Max. working height	3.50mm	110±25gf <2.1>	
Min. working height	3.20mm	140±35gf	
Durability	10000cycle		

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
<2.2>Warning: Working height are not permitted to be less than Min working height.
- 3 Electrical performance
Resistance: 30mOhm Max. Current rating: 2.0A
- 4 RoHS compliant.

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight	PART NUMBER	
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Qin Zuozhong	APVD:			110733-4	
0.0 = ±0.15		CHK:	REL:					
0.00 = ±0.10								
0.000 = ±0.05								
Angle: ±1°								
Angle: ±1°								
SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX. DO NOT SCALE PRINT.		Name	Customer drawing					
Scale	1:1	Size	A4	DWG No.	C-110733		Page	1/1
Rev.	Revision record.		Date.		Rev. 1			